

AQ380

The AQ380 uses Prolitec's patented AirQ technology to diffuse fragrance and odor canceling products into the air. This appliance was designed for commercial use to treat spaces directly, with various mounting configurations available. The included fan helps disperse the fragrance.



One-touch, digital display is very easy to use.

50 intensity levels and timing options give you control.

Perfectly scents spaces up to 15,000 cubic feet.

Tiny droplets convert to vapor within milliseconds.



Technical Specifications	Type	Single nebulizer head
	Cartridge	500 mL recyclable
	Droplet size	About one micron
Power Specifications	Input	100 – 240 VAC, 0.4A Max, 50/60 Hz
	Protection	Class 2 power supply
	Internal	Real time clock with permanent backup battery
	Output	15V DC at 1.2A
Performance & Settings	Coverage	Up to 15,000 ft ³ (425 m ³)
	Programs	Up to 21 start/stop times and intensities , 24/7 mode
	Settings	50 intensity levels
	Off-cycle	30 seconds, 2 minutes, or 7 minutes
	Enclosure	Polypropylene with locking door, white or black
	Safety Approval	CB, CE, & FCC Part 15, ROHS compliant
	Environment	0° to 40° C, <85% Humidity
Dimensions & Installation	Size	8½" x 8¾" x 4" (21.9 cm x 22.2 cm x 9.8 cm)
	Weight	5.4 lbs. (2.4kg) with full 500mL cartridge
	Mounting	Wall mount Tabletop, with feet Track light or ceiling mount Cable tie or pillar mount HVAC mount Through Wall mount Trash Chute mount

PROLITEC PERFECTLY SCENTED ENVIRONMENTS

PROLITEC sets the standard for enhancing indoor environments through fragrance.